



P.O. DRAWER 330 - DUNKIRK, MD 20754 USA TOLL FREE: (800) 368-2573 (USA & CANADA) TEL (301) 855-8300 - FAX (410) 257-7579 WEB SITE: HTTP://WWW.VICTORSTANLEY.COM


* ALL DIMENSIONS ARE IN MILLIMETERS *





INTEGRAL WELDED CROSS-MEMBERS
OF 48mm TUBULAR STEEL

33mm TUBULAR STEEL RUNG
USED FOR ADDITIONAL SUPPORT



CENTER-TO-CENTER DISTANCES ARE APPROXIMATE
(VARIATIONS IN CASTINGS ARISE FROM DIFFERENT RATES OF COOLING)

AVAILABLE OPTIONS:

POWDER COATING

10 STANDARD COLORS, 2 OPTIONAL METALLIC COLORS, CUSTOM COLORS (INCLUDING THE RAL RANGE)

CUSTOM PLAQUES

ENGRAVED CAST BRONZE PLAQUES

INTERMEDIATE & CENTER ARMRESTS

1.2 METERS, 1.8 METERS, & 2.4 METERS AVAILABLE WITH OPTIONAL ARMRESTS LENGTHS

STANDARD 1.2 METERS LENGTH SHOWN

STANDARD 1.8 METERS

STANDARD 2.4 METERS

NOTES:

- 1. DUCTILE IRON CASTINGS COME WITH A TEN YEAR WARRANTY AGAINST BREAKAGE.
- 2. DRAWINGS NOT TO SCALE. DO NOT SCALE DRAWINGS.
- 3. ALL FABRICATED METAL COMPONENTS ARE STEEL SHOTBLASTED, ETCHED, PHOSPHATIZED, PREHEATED, AND ELECTROSTATICALLY POWDER-COATED WITH T.G.I.C. POLYESTER POWDER COATINGS. PRODUCTS ARE FULLY CLEANED AND PRETREATED, PREHEATED AND COATED WHILE HOT TO FILL CREVICES AND BUILD COATING FILM. COATED PARTS ARE THEN FULLY CURED TO COATING MANUFACTURER'S SPECIFICATIONS. THE THICKNESS OF THE RESULTING FINISH AVERAGES 8-10 MILS (200-250 MICRONS).
- IT IS NOT RECOMMENDED TO LOCATE ANCHOR BOLTS UNTIL BENCH IS IN PLACE. THIS VICTOR STANLEY, INC. PRODUCT
 MUST BE PERMANENTLY AFFIXED TO THE GROUND. CONSULT YOUR LOCAL CODES FOR REGULATIONS.
- 5. ANCHOR BOLTS NOT PROVIDED BY VICTOR STANLEY, INC.
- 6. FOR HIGH SALT ABUSIVE CLIMATES, HOT DIP GALVANIZING BEFORE POWDER COATING IS AVAILABLE. SEE WRITTEN SPECIFICATIONS FOR DETAILS.
- 7. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE. CONTACT MANUFACTURER FOR DETAILS.
- 8. THIS PRODUCT IS SHIPPED FULLY ASSEMBLED.



BENCH WITH DUCTILE IRON END FRAMES SHOWN: STANDARD 1.2 METERS LENGTH